

Technical Data Sheet

C 701/TWIN

Order no.:	466 888																
Product designation:	Full Face Mask C 702/TWIN (Class 3) olive/black																
Applied standard:	DIN EN 136 (DIN = German Institute for Standardization)																
Utilization:	In connection with respiratory filter of the series 200 (special thread 66mm) as filtering device. The scope of protection is determined by the product information, technical standards and valid application rules.																
Description:	Faceblank enclose the entire face.																
Materials:	<table><tr><td>Faceblank</td><td>TPR (Thermoplastic Rubber)</td></tr><tr><td>Head harness</td><td>EPDM (Ethylene-Propylene-Diene-Mixture)</td></tr><tr><td>Inner mask</td><td>TPR (Thermoplastic Rubber)</td></tr><tr><td>Disk-Frame</td><td>Polyamide</td></tr><tr><td>Lens</td><td>Polycarbonate</td></tr><tr><td>Inhalation valve</td><td>Silicone</td></tr><tr><td>Connector</td><td>Fiberglass reinforced polyamide</td></tr><tr><td>Connector-Clip</td><td>Fiberglass reinforced polyamide</td></tr></table>	Faceblank	TPR (Thermoplastic Rubber)	Head harness	EPDM (Ethylene-Propylene-Diene-Mixture)	Inner mask	TPR (Thermoplastic Rubber)	Disk-Frame	Polyamide	Lens	Polycarbonate	Inhalation valve	Silicone	Connector	Fiberglass reinforced polyamide	Connector-Clip	Fiberglass reinforced polyamide
Faceblank	TPR (Thermoplastic Rubber)																
Head harness	EPDM (Ethylene-Propylene-Diene-Mixture)																
Inner mask	TPR (Thermoplastic Rubber)																
Disk-Frame	Polyamide																
Lens	Polycarbonate																
Inhalation valve	Silicone																
Connector	Fiberglass reinforced polyamide																
Connector-Clip	Fiberglass reinforced polyamide																
Weight:	approx. 620 g																
Inhalation resistance:	at 30 l/min, constant flow max. 0.5 mbar (EN 136) at 95 l/min, constant flow max. 1.5 mbar (EN 136) at 160 l/min, constant flow max. 2.5 mbar (EN 136)																
Exhalation resistance:	at 160 l/min, constant flow max. 3.0 mbar (EN 136)																
Marking:	Trade mark of manufacturer (LOGO) Product designation Applied standard Manufacture year and -month CE-Identification Notified body Type identifying marking																
Handling:	Take the Full face mask from the Packing and/or Storage container directly before use. Use the Full face mask in accordance with the information brochure.																
Storage conditions:	Ambient temperature. Protect against cold, heat and humidity. Consider conditions noted on the packaging.																
Warning reference:	Please consider the information brochure!																
User references:	EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 'Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines'.																

TD 466888 English 01-10.22