

MATERIALS

- Faceblank: Ethylene-Propylene-Diene-Mixture (EPDM)
- Fastener for head harness: Polyamide (PA)
- Harness: Ethylene-Propylene-Diene-Mixture (EPDM)
- Inhalation valve: Rubber
- Exhalation valve: Rubber
- Exhalation valve fit: Plastic (ABS)
- Exhalation valve cap: Polyphenylene oxide (PPO)
- Connector: Polypropylene (PP)
- Sorbents: Impregnated active charcoal
- Particle filter: Microfiberglass, Cellulose fibers

WEIGHT

- approx. 00 g

MARKING

- Trade mark of manufacturer (LOGO)
- Product designation
- Applied standard
- Manufacture year and -month
- CE-Identification
- Notified body
- Type identifying marking

DONNING AND USING

- Take the Half mask from the Packing and/or Storage container directly before use
- Use the Half mask in accordance with the information brochure

STORAGE

- Ambient temperature. Protect against cold, heat and humidity
- Consider conditions noted on the packaging

CERTIFICATIONS

- The mask is certified according to EN 140
- For use with particle, gas and combined filters of the series 200 (special thread 66mm)
- Certified according to European Regulation (EU) 2016/425

USER REFERENCES

EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 „Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines“.

TD 433396 English_05-04.24



EKASTU Safety GmbH
Schänzle 8 • D-71332 Waiblingen
Germany

Tel.: +49(0)7151 975099-0
Fax: +49(0)7151 975099-30

Internet: www.ekastu.de
eMail: info@ekastu.de